



ACCESSORIES



TANK



BALLAST

TECHNICAL CHARACTERISTICS



TELESCOPIC HANDLE



REDUCER



USER REQUIRED FOR STARTING THE MACHINE



SPEED SELECTOR

PACKAGE



CARTON BOX

- Single rotating brush for grouting of floors with joints, for smoothing of mortar base, for polishing and sanding surfaces, for cleaning and treatment of Terracotta.
- Telescopic handle with adjustable tilt.
- Quick Change tools.

- Dual rotation speeds 55/110 rounds/min (66/132 for 60 Hz versions).
- For use with tools with a diameter from 40 cm (15 3/4") to 51 cm (20").
- Supplied with: hex key kit, user and maintenance manual.

MODEL SPECIFICATIONS

Part No.							
<b>122</b>	8024648004680	1	230 V 50 Hz	Single-phase	0,8 HP / 0,6 kW	1400 / 2800	55 / 110
<b>122 60HZ</b>	8024648006547	1	230 V 60 Hz	Single-phase	0,8 HP / 0,6 kW	1680 / 3360	66 / 132
<b>122GB110</b>	8024648004703	1	110 V 50 Hz	Single-phase	0,8 HP / 0,6 kW	1400 / 2800	55 / 110
<b>122US115</b>	8024648004710	1	110 V 60 Hz	Single-phase	0,8 HP / 0,6 kW	1680 / 3360	66 / 132

DIMENSIONS AND WEIGHT

Model				
<b>SUPERTITINA</b>	50x60xh 80 cm 20"x23"xh 31"	23 Kg 50.7 lbs	75x50xh 40 cm 29 1/2"x20"xh 15"	26 Kg 57.3 lbs

